

Super Flat Suspension 120x30 Up&Down Dali Version

■ 09.5045.14BDA - Black

General lighting LED luminaire, direct and indirect beam, to be suspended from ceiling. Power supply included.

General lighting LED luminaire, direct and indirect beam, to be suspended from ceiling. Power supply included.


Main specifications

Number of heads	1	Net lumen (lm)	4225
Lamp category	LED	Mountings	Suspension
Power	56W	Environment	Indoor
CCT	3000K		
CRI	90		



Optical


Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	109
Beam angle C90-270 (°)	91



Beam Angle DIR: 109°

h(m)	E(lx)	D(m)
1	632	2.82
2	158	5.64
3	70	8.46
4	40	11.27
5	25	14.09

Luminous flux luminaire
4225 lm (EXTREME CUT OFF)




Electrical

Frequency (Hz)	50/60	Insulation class	I
Voltage (V)	35.00		
Dimmable	Yes		
Driver	Integrated		
Emergency	Without		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	4.20

Certification / Marking



Note

Total consumption of the system: 56W. Light source: Up: max. 3482 lm. Down: max. 3482 lm. Luminous efficiency of luminaire: max. 138 lm/W.